

**NOTE:** For all available options see the On-Machine product catalog: M117-CA001

Ratings and additional options shown on back.

**ARMORSTART**  
284E-FVD4P0Z-10-RR-SB-3



**ARMORSTART LT**  
290E-FBZ-G2-3



**ARMORSTART LT**  
294E-FD2P5Z-G2-3




**POWER & DISTRIBUTION PANEL**



**1** ETHERNET M12 PATCHCORD  
**1585D-M4TBDM-2**  
Cable Style: TPE, flex rated, unshielded  
Assembly: 24 AWG, 4 pin  
Cable Diameter: 0.23 in (5.84 mm)

**2** RJ45 TO M12 D-CODE RECEPTACLE  
**1585D-D4TBJM-2**  
Cable Style: TPE, high flex, unshielded, twisted pair  
Assembly: 24 AWG, 4 Conductor  
Cable Diameter: 0.23 in (5.84 mm)




**FEMALE**

**MALE**

**M12 PINOUT**

- 1 White-Orange
- 2 White-Green

- 3 Orange
- 4 Green



**RJ45 8-PIN PINOUT**

- 1 White/Orange
- 2 Orange
- 3 White/Green
- 4 Blue
- 5 White/Blue
- 6 Green
- 7 White/Brown
- 8 Brown

**Rockwell Automation**

**ETHERNET NETWORK**

**QUICK REFERENCE GUIDE: 280-QR003A-EN-P**

1

**ETHERNET M12 PATCHCORD OPTIONS****1585D-M 4 T BD M- \*****Lengths:** See Key Below**Second End Connector:****M-** Male Straight**E-** Male Right Angle**F-** Female Straight (only with straight male first connector)**Jacket Material:****T-** TPE: 24 AWG**First End Connector:****M-** Male Straight**E-** Male Right-Angle

\*Lengths available in 0.3, 0.6, 1, 2, 5, 10, 15 and additional increments of 5m up to 75m.

**Assembly:** 24 AWG, 300 V

**Ratings:** IP67

2

**RJ45 TO M12 D-CODE RECEPTACLE**

**1585D-D4TBJM-\***: 4-Pin M12 D-Code Front Mount Receptacle to RJ45 Patchcord.

\*Lengths available in 0.3, 0.6, 1, 2, 5, 10, 15 and additional increments of 5m up to 75m.

**Ratings:** IP67



**1585A-DD4JD-** M12 Female to RJ45 Cat 5e Female Field Attachable.

**ETHERNET RJ45 PATCHCORD OPTIONS**

RJ45 Patchcords can be used in combination with a field receptacle in lieu of the RJ45 to M12 D-Code Receptacle.

**1585J-M 4 T BJM- \*****Lengths:** See Key**Jacket Material:****T-** Teal High Flex TPE**4-** 4 Conductors**8-** 8 Conductors

\*Lengths available in 0.3, 0.6, 1, 2, 5, 10, 15 and additional increments of 5m up to 75m.

**ADDITIONAL LENGTHS**

If additional lengths are desired use a cable spool and RJ45 Crimp connector

**RJ45 CRIMP CONNECTOR WITH BOOT:** 1585J-M8CC-C 150 V, 1.5 A

**CABLE SPOOL****RJ45 CRIMP****ADDITIONAL OPTIONS**

Additional Options such as jacket material, conductors, and shielding are available. See the On-Machine Connectivity Products Catalog or contact your local Allen-Bradley distributor.

**BILL OF MATERIALS**

Qty	Catalog #	Description
<b>Ethernet Media</b>		
4	1585D-M4TBDM-2	Ethernet M12 Patchcord
2	1585D-D4TBJM-2	RJ45 to M12 D-Code Receptacle

\*Bill of materials pictured in diagram, only to be used as an example.